



Farabaugh Engineering and Testing Inc.

FET Project No. T346-12A

Date: October 5, 2012

Revised May 21, 2018

Performance Test Summary

TAS-100A

Test Procedure for wind and Wind Driven Rain Resistance and/or Increased Windspeed Resistance of
Soffit Ventilation Strip and Continuous or Intermittent Ventilation System Installed at the Ridge Area

On

EZ Vent-N-Closure

For

Vent-A-Roof

38 Nuemann Rd.

Capalaba Q 4157

Australia

Daniel C. Farabaugh,

Farabaugh Engineering and Testing Inc.



ACCREDITED
LABORATORY



ACCREDITED
LABORATORY



ACCREDITED
LABORATORY



TEXAS DEPARTMENT
OF INSURANCE
ACCREDITED LABORATORY

Purpose

The purpose of this testing of Custom Metal Components, Inc.'s "EZ Vent-N-Closure" in accordance with the following testing standard:

- 1) TAS-100A to establish the resistance to wind driven rain of a continuous or intermittent ridge area ventilation system when installed in a discontinuous roof system.

Test Summary

Custom Metal Components, Inc.'s EZ Vent-N-Closure metal roof ridge ventilation system for metal buildings has passed the windspeed and water spray intervals for wind driven rain resistance testing.

Intervals	Wind Speed (MPH)		Water Spray Rate		Water Spray	Time (MIN)	Observations
	(MPH)	(KM/H)	(IN/HR)	(MM/HR)			
1	35	56.3	8.8	223.5	ON	15	PASS(0 mL)
2	0	0	-	-	OFF	5	-
3	70	112.6	8.8	223.5	ON	15	PASS (0 mL)
4	0	0	-	-	OFF	5	-
5	90	144.8	8.8	223.5	ON	15	PASS (<1 mL)
6	0	0	-	-	OFF	5	-
7	110	177	8.8	223.5	ON	5	PASS (<1 mL)
8	0	0	-	-	OFF	5	-

Total Volume of Water Collected: Less Than 1 mL (Allowable 415 mL-Pass)